



FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8




FIG. 9

LIGHTING REQUIREMENT		AVERAGE	MAX	MIN	DEFORMATION OF FILAMENT
BLINKING	CONTINUOUS ILLUMINATION	619.6	878.8	287.6	NONE
	(a) NO DIMMING	470.1	559.5	400.4	NONE
	(b) DIMMING DURING EXTINCTION	41.6	50.4	33.2	DEFORMED
	2sec.	274.8	490.1	114.7	DEFORMED
	1sec.	420.2	679.2	298.8	DEFORMED
(c) VOLTAGE SWITCHING	0.5sec.	486.6	638.5	393.3	NONE
	STOPWISE DIMMING	254.3	499.0	79.6	DEFORMED
	14/6V	38.9	49.9	26.7	DEFORMED
	14/7V	18.9	25.7	6.2	DEFORMED
	14/8V	62.6	116.6	24.1	DEFORMED
	14/9V	250.0	280.0	138.9	SLIGHTLY DEFORMED
	14/9.5V	514.5	667.0	308.5	NONE AT THIS TIME
14/10V					

FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B

